

3M Science.
Applied to Life.™

3M™ High Performance Masking Tape 401+

Industrial strength performance you can trust.

For demanding industrial paint masking operations, 3M™ High Performance Green Masking Tape 401+ is an obvious choice. It delivers super-sharp paint lines with strong hold and clean removal in masking applications where surface temperatures reach up to 250°F (121°C) for up to 30 minutes. Designed to deliver consistent performance for high-temperature paint baking and fascia painting, this highly visible tape can also help improve accuracy during paint masking. When you consider 401+ can also be used to accomplish everything 3M™ Industrial Masking Tapes 101+, 201+ and 301+ can do, it's quite possibly the most versatile tape in the line.



Smooth unwind

Easy, controlled unwind reduces worker fatigue, improving productivity.



Temperature resistant

Resists bleed-through and withstands surface temperatures up to 250°F (121°C) for up to 30 minutes for masking applications that include a bake cycle.



Sharp paint lines

Delivers sharp, clean paint lines and is ideal for high-temperature paint baking or fascia painting.



Strength + performance

Superior adhesion and holding power on metal, rubber, glass and plastic, while removing cleanly in one piece with no adhesive residue.



Industrial-strength masking.

When you're looking for a tape that can handle demanding industrial paint masking operations, look no further than 3M™ High Performance Green Masking Tape 401+. For more information on 3M Masking Solutions, contact your local 3M representative or call 1-800-362-3550 or visit 3M.com/masking.



Product	UPC#	Width	Length	Rolls/Case
3M™ High Performance Green Masking Tape 401+ Bulk	00-051115-69109-6	6 mm	55 m	96
	00-051115-64759-8	12 mm	55 m	48
	00-051115-64760-4	18 mm	55 m	48
	00-051115-64761-1	24 mm	55 m	24
	00-051115-64762-8	36 mm	55 m	16
	00-051115-64763-5	48 mm	55 m	12
	00-051115-64764-2	72 mm	55 m	8
	00-051115-64765-9	96 mm	55 m	8
3M™ High Performance Green Masking Tape 401+ Individually Wrapped	00-051115-64766-6	1490 mm	55 m	1
	00-051115-64767-3	24 mm	55 m	24
	00-051115-64768-0	36 mm	55 m	16
	00-051115-64769-7	48 mm	55 m	12

Specifications

Total Thickness: 6.4 mil (.16 mm)
 Adhesion to Steel: 35 oz/in (3.8 N/cm)
 Tensile Strength: 24 lb/in (42 N/cm)
 Elongation at Break: 14%



Closure and Masking Systems Division

3M Center, Building 225-3S-06
 St. Paul, MN 55144-1000
 800-362-3550 877-369-2923 (Fax)
3M.com/masking

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for proper evaluation (including, but not limited to, fitness for purpose and suitability of application), selection, and use of 3M products. Safety products should always be selected and used in accordance with all applicable regulations and standards (e.g., OSHA, ANSI, and others), after conducting a proper hazard assessment. Failure to properly evaluate, select, and use a 3M product may result in injury, sickness, death, and/or harm to property. Dispose of used atomizing heads, residual paint/coatings, used containers/materials, and PPS in accordance with local regulations.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

3M is a trademarks of 3M Company. Please recycle. Printed in USA.
 © 3M 2021. All rights reserved. 70-0716-1677-8 REV 8/21